AUTOMATIC TAPING MACHINE - CONDOR









Condor is an automatic machine that places an adhesive tape around various loose products, also delicate. The products are positioned manually on slots called "cradles", that are installed on a pair of chains that move together. Operators can load the products from the back or from the sides of the machine. Once loaded, the products are moved towards the taping position and finally evacuated on a soft wave belt. Condor is very flexible and can be configured with 1 or 2 distributors of tape (that can be located in a central position or on the sides) and with various kinds of cradles. It's totally built in stainless steel (with the exception of the distributors of tape), IP55.

Suitable for processing elongated products in bundle (bananas, leek, celery) and also round products (melons, coconuts, pineapples, small watermelons).

PLUS:

- · Fast and gentle
- · Easy and intuitive to operate
- · Easy to sanitize

Details:

- 4.3" color touch screen control panel
- · Works with PP, paper or compostable adhesive tape; dual-component or direct adhesive tape
- Tape dispenser with rewind mechanism for paper and with end-of-tape sensor
- Tape dispenser capacity (per channel): 620 m (about 44 minutes working time)
- Tape width: from 19mm to 38mm
- Sensor for loaded product, for production optimization
- Double independent taping mechanisms, configurable on the touch screen
- Max product height: 200 mm
- Product width: Max. 370 with 2 channels / Min. 90 mm
- Diameter standard cradles: 160mm
- No product weight limit
- Built in stainless steel (with the exception of the distributors of tape), IP55
- High production continuity; low maintenance required
 Low power consumption (1,5Kw)
- Control panel can be located on the right hand side or on the left hand side (standard is left hand side)
- · Machine weight (heaviest configuration): 705 kg
- Dimensions for transport: 4400x1100x2000 mm (LxWxH)
- Max production speed: 52 pcs/min (with 2 feeding lines) or 26 pcs/min (with 1 feeding line)

OPTIONALS:

- Installation on wheels (H +30 mm)
- Weight-and-price system with adhesive label applicator

