

EAGLE AUTOMATIC TAPING MACHINE



FAST, RELIABLE AND FLEXIBLE
EASY AND INTUITIVE TO USE

COMBINABLE WITH PRE-EXISTING LINES



- Eagle is an automatic machine born for applying an **adhesive-tape band to loose products**.
- The products are manually loaded on specific compartments called "cradles". The cradles are mounted on a pair of chains which advance simultaneously. The operators in charge of the loading can be positioned on the machine rear and/or on both sides. Once loaded, the product is carried towards the taping station and then ejected.
- **Ideal for:** spherical products such as melons, small watermelons, pineapples and coconuts.

TECHNICAL FEATURES

- 4,3" colour touch-screen panel
- Possibility of using PP, paper, compostable, peelable or self-adhesive tape
- Tape dispenser with peel rewinder and end-of-material-detection sensor
- Tape capacity (each channel): 620 m (about 44 minutes of autonomy)
- Sensor for detecting the passing of the product maximum height
- Sensor for detecting the product presence, in order to optimise production
- Tape application in case of product presence only (automatically and for each channel)
- Independent taping devices selectable from the interface
- Recommended-load indicator light, for minimising the tape consumption on both channels equally
- Maximum product height: 200 mm
- Product width: max 270 / min 85 mm
- No product weight limits

REV PACKAGING SOLUTIONS S.R.L.
Via F. Parri, 745 – 47522 Cesena (FC), Italy
+39 0547 384 435 · info@revsrl.com · www.revsrl.com

REV
packaging solutions

EAGLE AUTOMATIC TAPING MACHINE

- Parts touching the product made of materials suitable for food contact
- High production continuity and minimum maintenance
- Extremely low energy consumption
- Compact size
- Possibility of symmetrical mounting (whether not specified, the machine is intended with the operator panel on the left)
- Maximum-configuration weight: 428 kg
- Machine size for the transport: 3300x900x1850 mm (LxWxH)
- Maximum production: 56 o 28 pcs/min. (with 1 or 2 lanes)

OPTIONS

- Mounting on wheels (H +30 mm)
- Weigh-price device with adhesive-label applicator