

S-CLIP SEMI-AUTOMATIC CLIPPING MACHINE



**SOLID AND WIDELY CONFIGURABLE
USING A PROFESSIONAL CLIPPING HEAD**

COMBINABLE WITH ALL MACHINES



- S-Clip is a simple and solid machine for manually closing different-product packages by means of **tubular net and a metal clip**.
- The product to be packaged has to be loaded on the net tube (if any) and, with a simple move, the device applies the clip and simultaneously cuts the net; the machine is thus ready for the following cycle.
- S-Clip can be equipped with a **device for attaching wineglass labels** and an electronic printer, for indicating on the label all necessary information (bar code, production lot, etc.). Moreover, it is possible to add to the package a **tape functioning as handle** and to the machine a net tube.
- S-Clip is provided with an electrical panel with **alarm management through PLC**. The clipping-head motor is controllable by means of an inverter (as in all most advanced automatic netting machines) and is activatable through a lever with safety lock for avoiding clippings on repeat.
- **Ideal for:** garlic, onions, etc. (all products usually packaged in net).

TECHNICAL FEATURES

- Pneumatic and mechanical drive
- Electrical panel with alarm management (label or strap exhaustion and clip jam) by means of PLC
- Clip engine manageable through inverter
- Package closing with traditional metal clip in bobbin (5×0.30÷0.35 mm)
- Metal clip in Ø360-mm bobbin
- Toshiba high-resolution wineglass-label printer, with alarm management and label data storage
- Possibility of using labels of different lengths

REV PACKAGING SOLUTIONS S.R.L.
Via F. Parri, 745 – 47522 Cesena (FC), Italy
+39 0547 384 435 · info@revsrl.com · www.revsrl.com

REV
packaging solutions

S-CLIP SEMI-AUTOMATIC CLIPPING MACHINE

- Parts subject to dirt in AISI 304 stainless steel and anodised aluminium, for an easy sanitisation
- Tape / handle width: from 12 mm to 30 mm
- Available net-tube diameters: Ø70, Ø80, Ø100, Ø140, Ø160, Ø200, Ø250 mm
- Drive by means of pedal (optional) or lever, with anti-repetition safety lock
- Extreme ease of use
- Installed power: 0,33 kW
- Voltage: 230 V 50 Hz + PE
- Air consumption: 50 NI at 6 bar
- Length: 800 mm
- Weight: 90 kg
- Potentiality: up to 30 packages/min. (according to the operator's skills)

OPTIONS

- Kit of package handle tape